




STAHLIE IMPORT B.V.

Onderdelen - Accessoires - Gereedschappen

	<p>BOSCHMANN Versteker</p> <p>XR222</p> <p>2 kanaals Mosfet versterker Max vermogen: 800W @ 20hm Brugbaar vermogen (RMS): 250W x 1ch @ 40hm Continue vermogen: 125W x 2ch @20hm Freq Resp: 5HZ-50kHz High pass filter freq: 80Hz-1.2kHz Low pass filter freq: 50Hz-250 kHz Bass Boost: 0dB/6dB/12dB</p>
	<p>BOSCHMANN Versteker</p> <p>XR888</p> <p>4 kanaals Mosfet versterker Max vermogen: 1200W Brugbaar vermogen (RMS): 200W x 2ch @ 40hm Continue vermogen (RMS): 95W x 4ch @ 20hm Freq Resp: 5Hz-50kHz High pass freq: 80Hz-1.2kHz Low pass freq: 50Hz-250kHz Bass Boost: 0dB/6dB*12dB</p>
	<p>BOSCHMANN Versteker</p> <p>PSXD1</p> <p>Dual mono block versterker Max vermogen: 3300Watt RMS vermogen: 2 x 800w (40hm) Variable Filter: Low-pass 50-250Hz Subsonic 20-50Hz Input sensitivity: 240mV ~ 4V Afmetingen: 290 x 60 x 380mm Remote Level Control included</p>
	<p>BOSCHMANN Versteker</p> <p>JX3DQZ</p> <p>Monoblok Class 'D' Max vermogen RMS: 1800W @1ohms Max vermogen RMS: 1000W @2ohms Max vermogen RMS: 500W @4ohms Max vermogen: 3800W @1ohms Freq. bereik (@±1dB): 5Hz-250Hz Low pass filter freq.:50Hz-250Hz (@24dB) var. High pass filter freq.:80Hz-1.2kHz (var.)</p>